

## Robulon PP Technical Data

TenCate Geolon® Robulon PP is a high strength geocomposite for erosion control purposes. The product is made of 100% highly durable and UV resistant PP, with a 3 dimensional structure. The combination of reinforcement and soil retention makes Robulon the ideal mat for erosion control in a variety of applications such as protection of slopes, geomembranes, canal and river beddings, and shorelines.



TenCate Geolon® Robulon PP

Characteristics <small>[Standard]</small>	Unit	PP 40	PP 60	PP 80	
<b>Type of product</b>		Geocomposite made of 100% polypropylene, consisting of a high strength woven base layer featuring inseparable loops for soil, gravel or concrete retention.			
<b>Product Properties</b>					
Mass per unit area <small>[EN ISO 9864]</small>	g/m <sup>2</sup>	510	580	675	
Thickness under 2kPa <small>[EN ISO 9863-1]</small>	mm	10	10	10	
UV resistance (retained tensile strength) <small>[EN ISO 12224]</small>	%	> 80	> 80	> 80	
<b>Base Layer Properties</b>					
Tensile strength <small>[EN ISO 10319]</small>	MD*	kN/m	40	63	84
	CD*	kN/m	40	57	84
Elongation at maximum strength <small>[EN ISO 10319]</small>	MD*	%	17	8	8
	CD*	%	12	8	8
CBR Puncture Resistance <small>[EN ISO 12236]</small>		kN	4	6	8
Dynamic Perforation <small>[EN ISO 13433]</small>		mm	15	10	9
<b>Forms of supply</b>					
Width	m	5	5	5	
Length	m	50	50	50	
Roll diameter	m	0.8	0.85	0.85	
Roll weight (± 10%)	kg	140	160	180	

\* MD = Machine Direction CD = Cross Direction

The values given are average values obtained in our laboratories and in testing institutes. The right is reserved to make changes without notice at any time.

**TENCATE GEOSYNTHETICS AUSTRIA Ges.m.b.H.**  
Schachermayerstrasse, 18 - A - 4021 Linz - Austria  
Tél. +43 732 6983 0, Fax +43 732 6983 5353  
service.at@tencate.com, www.tencategeosynthetics.com

BeNeLux  
Central Eastern Europe  
Czech Republic  
France / Africa  
Germany  
Italy  
Near Middle East

Tel. +31 546 544 811  
Tel. +43 732 6983 0  
Tel. +420 2 2425 1843  
Fax +33 1 34 23 53 48  
Tel. +49 6074 3751 50  
Tel. +39 0362 34 58 11  
Tel. +971 4810 3295

service.nl@tencate.com  
service.at@tencate.com  
service.cz@tencate.com  
service.fr@tencate.com  
service.de@tencate.com  
service.it@tencate.com  
service.nme@tencate.com

Poland  
Russia / CIS  
Scandinavia / Baltics  
Spain / Portugal  
Turkey  
UK / Ireland

Tel. +48 12 268 8375  
Tel. +43 732 6983 0  
Tel. +31 546 544 811  
Tel. +34 607 499 962  
Tel. +43 732 6983 0  
Tel. +44 1952 588 066

service.pl@tencate.com  
service.ru@tencate.com  
geonordic@tencate.com  
service.es@tencate.com  
service.tr@tencate.com  
service.uk@tencate.com



Quality - Environment  
ISO 9001  
ISO 14001  
www.dekra.com

503 068 | 10/2015 EN  
891 406 DJ - ASU

Protective Fabrics  
Outdoor Fabrics  
Advanced Composites  
Advanced Armour

Geosynthetics  
Grass